


DARK ROUND TRIMLESS 60







LUMINAIRE SPECIFICATION

Height	Refer to line drawing
Bezel	Ø55mm
Hole cut-out	Back of ceiling : Ø58mm Front of ceiling : Ø60mm
Luminaire material	Aluminium with textured powder coat finish.
Light source	COB LED
Optics	Interchangeable lens & reflectors
Driver	Remote
IP Rating	IP20 and IP44 options
Optional accessories	Honeycomb louvre Solite lens Spread lens
Allow 3mm of additional height per accessory	

LED SPECIFICATION

LED	Citizen high intensity
Source LED output	4.5W 460lm 6.3W 598lm
Typical delivered output	4.5W 458lm 6.3W 593lm
CCT	2700K, 3000K, 4000K
CRI	>90Ra
Binning	2 Step
Optics	15°, 25°, 35°, 50°
Lifetime (L70)	>50,000 hrs based on LM-80 and TM-21 manufacturers applicable test data
Driver requirement	Constant current
Drive current	4.5W : 500mA 6.3W : 700mA
Forward voltage	9VDC

REFLECTOR OPTIONS

			
SILVER CHROME	DARK CHROME	MATT WHITE	MATT BLACK

ORDERING INFORMATION

example 23233L35.1SC32A5C-FC

BEAM ANGLE	FINISH	REFLECTOR	LED CCT	DRIVER	VERSION	IP RATING	MOUNTING	ACCESSORIES
23233L15 15°	1 White	SC Silver chrome	2 2700K	1 Non dimming	A5C 4.5W CRI >90	IP20	-BC Back of ceiling	-H Honeycomb louvre
23233L25 25°	2 Black	DC Dark chrome	3 3000K	2 Phase dimming	A6C 6.3W CRI >90	4 IP44	-FC Front of ceiling	-SO Solite lens
23233L35 35°	7 Silver	MB Matt black	4 4000K	3 0-10V dimming				-SL Spread lens
23233L50 50°		MW Matt white		4 DALI dimming				